

Study of the effects of a distanced retention basin combined with an open check dam on a physical model

Sebastian Schwindt, MSc¹; Guillaume Piton, Ing.²; Giovanni De Cesare, Dr.³; Alain Recking, Dr.²; Anton J. Schleiss, Prof. Dr.³

INTRODUCTION

Sediment traps are thus classically used in flood hazard mitigation (Zollinger, 1983; Ghilardi et al., 2012). Typical sediment traps consist of an upstream basin combined with an open check dam at the outlet (Fig. 1 a). However, in some cases spatial or geotechnical constrictions do not allow for the construction of one of the two elements. It is possible to limit the structure to a simple basin without open check dam when the space is sufficient, as the longitudinal bed slope can be reduced by levelling the river, thus enhancing the process of sediment deposition (e.g. Kaitna et al., 2011). In steep narrow valleys or due to anthropogenic infrastructures, there is sometimes not enough space available for a basin. An open check dam without widened basin has to be considered in this case. Sediments are then stored directly in the river bed upstream of the structure. In some particularly critical cases, i.e. when it is neither possible to implement a sufficiently large retention basin, nor a big enough open check dam, a combination of an open check dam with a retention basin built at a given distance is conceivable (Fig. 1 b). This kind of situation has been analyzed with the physical model of the Drance river, upstream of Martigny in the upper Rhone valley (Switzerland). The paper presents in which extend it had been possible to achieve the mitigation objective using this specific configuration.

CONTEXT

The Drance river has several debris flow prone tributaries before it passes the town of Martigny. During severe floods, as occurred in 2000, the tributaries supply significant sediment amounts to the main-stem. The Drance then transports the sediments downstream which aggravate the flood hazard in the city of Martigny. The creation of a sediment trap downstream of the tributary conflu-

ences and upstream of the area to protect has been studied using small scale experiments.

As the tributaries are situated close to the city, few sites exist for the implementation of the sediment trap where not enough space is available to create a classical structure (Fig. 1 a). The installation of an open check dam, with an upstream distanced basin creates a storage volume by means of a trap basin and a 100 m long channel section between the check dam and the basin.




Figure 1. Concept of sediment traps: a) the classical scheme, i.e. the check dam is directly connected with the basin and b) the herein studied scheme, i.e. the retention basin is situated at some distance upstream of the open check dam. The different processes that control deposition are illustrated by ① ② ③ ④ and commented in the text.

OBJECTIVES

Four different effects lead to sediment deposition in sediment trap basins (Zollinger, 1983; Piton and Recking, 2015). Two of them are related to the basin feature:

1. decrease in sediment transport capacity due to milder slopes in the basin;
2. decrease in sediment transport efficiency due to flow spreading in the basin which is wider than the upstream channel.

And the two other effects are induced by the open check dam:

3. open check dam backwater effect inducing a drop in shear stresses in the tranquil water area and;
4. mechanical blockage of coarse elements against the open check dam. In this case the distance of 100 m between the sediment trap outlet and the basin could disconnect the system. Therefore, a small scale model is used to analyze this system.

METHODOLOGY

The physical model has already been tested for the hydraulic functioning of an open check dam only. The reproduced river section is about 800 m long, where the average bed slope is about 2.4 % and the width of the main channel varies between 10 m and 15 m in prototype dimensions. The height of the check dam is limited due to railway line on the right river bank. The expected amounts of sediments to be retained as well as the grain size distribution are subjected to some uncertainty. About 100 m upstream of the check dam, it is possible to implement a retention basin of the shape of a deposition area. The effects of this retention basin on sediment transport in the Drance were analyzed by experiments with discharges of the order of an annual flood, a 100 - years flood and the average river discharge. Sediments were added continuously at the model inlet and in shape of a debris flow deposition from another lateral torrent which is situated about 700 m upstream of the check dam.

RESULTS

The retention reservoir enhanced the sediment deposition upstream of the open check dam and reduced the sediment transported towards the open check dam at the beginning of a flood event. Once the bed slope in the deposition area reached an equilibrium state, the natural bed load transport continuity reestablished and entered the channel between the open check dam and the basin. In this reach, closer to the open check dam, the backwater effects enhanced the deposition of sediments which were then trapped during the backfilling process in front of the check dam. This backfilling was sufficient enough to reach the retention basin, thus increasing the deposition in this area.

KEYWORDS

Retention reservoir; Open check dam; Sediment deposition; Bed load

CONCLUSIONS

A deposition area in some distance upstream, but still in the influence region, of an open check dam has been proven to increase the sediment storage capacity compared with the construction of an open check dam only. The combination of the two measures, i.e. a bed load trap in two separated structures therefore represents a remedy in case of spatial constrictions.

LITERATURE

- Ghilardi T., Boillat G.J.-L., Schleiss A.J., De Montmollin G., Bovier S. (2012). Gestion du risque d'inondation sur l'Avançon par rétention de sédiments - optimisation sur modèle physique [Flood risk management of the Avançon river by means of sediment retention - physical model based study], in: Proceedings of the 12th Interpraevent Congress, 23-29 April 2012, Grenoble, 687-698.
- Kaitna R., Chiari M., Kerschbaumer M., Kapeller H., Zlatić-Jugović J., Hengl M., Hübl J. (2011). Physical and numerical modelling of a bedload deposition area for an Alpine torrent. *Natural Hazards and Earth System Science* 11, 1589-1597.
- Piton G., Recking A. (2016). Design of sediment traps with open check dams. I: hydraulic and deposition processes *Journal of Hydraulic Engineering*, 142, 1-23.
- Zollinger F. (1983). Die Vorgänge in einem Geschiebeablagerungsplatz: ihre Morphologie und ihre Möglichkeiten einer Steuerung. PhD thesis, Eidgenössische Technische Hochschule Zürich.

1 Ecole Polytechnique Fédérale de Lausanne, Lausanne, SWITZERLAND, sebastian.schwindt@epfl.ch

2 Irstea - Université Grenoble Alpes, St Martin d'Hères, France

3 Laboratoire de Constructions Hydrauliques - École Polytechnique Fédérale de Lausanne, Lausanne, SWITZERLAND