

# A Unified Framework for Max-Min and Min-Max Fairness with Applications

Božidar Radunović and Jean-Yves Le Boudec, *Fellow, IEEE*,

**Abstract**—Max-min fairness is widely used in various areas of networking. In every case where it is used, there is a proof of existence and one or several algorithms for computing it; in most, but not all cases, they are based on the notion of bottlenecks. In spite of this wide applicability, there are still examples, arising in the context of wireless or peer-to-peer networks, where the existing theories do not seem to apply directly. In this paper, we give a unifying treatment of max-min fairness, which encompasses all existing results in a simplifying framework, and extend its applicability to new examples. First, we observe that the existence of max-min fairness is actually a geometric property of the set of feasible allocations. There exist sets on which max-min fairness does not exist, and we describe a large class of sets on which a max-min fair allocation does exist. This class contains, but is not limited to the compact, convex sets of  $\mathbb{R}^N$ . Second, we give a general purpose centralized algorithm, called Max-min Programming, for computing the max-min fair allocation in all cases where it exists (whether the set of feasible allocations is in our class or not). Its complexity is of the order of  $N$  linear programming steps in  $\mathbb{R}^N$ , in the case where the feasible set is defined by linear constraints. We show that, if the set of feasible allocations has the free-disposal property, then Max-min Programming reduces to a simpler algorithm, called Water Filling, whose complexity is much lower. Free disposal corresponds to the cases where a bottleneck argument can be made, and Water Filling is the general form of all previously known centralized algorithms for such cases. All our results apply *mutatis mutandis* to min-max fairness. Our results apply to weighted, unweighted and util-max-min and min-max fairness. Distributed algorithms for the computation of max-min fair allocations are outside the scope of this paper.

©2006 IEEE. Personal use of this material is permitted. However, permission to reprint/republish this material for advertising or promotional purposes or for creating new collective works for resale or redistribution to servers or lists, or to reuse any copyrighted component of this work in other works, must be obtained from the IEEE. The work presented in this paper was supported (in part) by the National Competence Center in Research on Mobile Information and Communication Systems (NCCR-MICS), a center supported by the Swiss National Science Foundation under grant number 5005-67322. Authors are with EPFL, CH-1015 Lausanne, Switzerland (email: bozidar.radunovic@epfl.ch, jean-yves.leboudec@epfl.ch)

## I. INTRODUCTION

### A. Max-min Fairness

Max-min fairness is a simple, well-recognized approach to define fairness in networks [7]; it aims at allocating as much as possible to users with low rates, and, at the same time, not unnecessarily wasting resources (see Section II-A for a formal definition). It was used in window flow control protocols [9], then became very popular in the context of bandwidth sharing policies for ABR service in ATM networks [3]. It is now widely used in various areas of networking [26], [28], [27], [12], [10], [8], [17], [15], [9], [1].

One of the simplest max-min fairness examples, given in [7], is single-path rate allocation. Suppose we have a network consisting of links with fixed capacities, and a set of source destination pairs that communicate over a single path each, and with fixed routing. The problem is to allocate a rate to each source-destination pair, while keeping the rate on each link below capacity. Here, we call a rate allocation max-min fair if one cannot increase the rate of a flow without decreasing the rate of an already smaller flow. A set of feasible rate allocations for a simple two source example is given in Figure 1. A definition dual to a max-min fair allocation is min-max fair allocation, and is used in the context of workload distribution, where the goal is to spread a given workload evenly to all the parties (see [14]) and where rates have to be allocated to available links as evenly as possible.

### B. Microeconomic Approaches to Fairness

Microeconomic theories of social welfare functions and social optima discuss a fair choice of alternatives (such as goods distribution or policy making) [2]. Each possible alternative is assigned a utility, that represents its value to each individual in the system. A social welfare function is a way to aggregate individual utilities into a social utility. The optimal choice of the alternative is the one that maximizes the social welfare function [2].

There are numerous ways to define social welfare functions. One is a maximin or Rawlsian social welfare function [21] that maximizes the utility of the worst-off individual. It has been widely used in the design of communication systems (see for example [16]).

The main problem of the maximin social welfare function is that the optimal alternative is not necessarily Pareto optimal. In other words, starting from the maximin optimal alternative one can increase the utility of one individual without decreasing utilities of the others, and this is clearly not a desirable property of an efficient alternative.

A leximin social welfare ordering is a refinement of the maximin social welfare function [5], [4]. It is based on the notion of the *leximin ordering*: one vector is said to be leximin larger or equal than the other if its ordered permutation is lexicographically larger or equal to the ordered permutation of the other vector (a precise definition is given in Definition 4 in Section II-B). The leximin social welfare optimum is always Pareto optimal [2].

The fairness criteria in networking are based on findings from social welfare theory. Max-min fairness is closely related to leximin ordering. We discuss this issue in depth in Section II-B.

Another important concept from microeconomics used in this paper is the *free disposal property*. In economics, it is defined as the right of each user to dispose of an arbitrary amount of owned commodities [2], or alternatively, to consume fewer resources than maximally allowed. The formal definition is given in Definition 6 in Section III-B.

### C. Bottleneck and Water-Filling

Most of the existing works on max-min fairness rely on the notion of bottleneck link. Referring again to the single-path rate allocation example given in Figure 1, we say that a link is a bottleneck for a given flow if the flow uses the link, if the link is fully utilized, and if the flow has the maximal rate among all the flows that use the link (see [7] for the exact definition). It is shown in [7] for the above example that if each flow has a bottleneck link, then the rate allocation is max-min fair. This finding, which we call the bottleneck argument, is often used to prove the existence of max-min fairness.

The most widely used algorithm for obtaining max-min fairness is the *water-filling* algorithm (WF) [7]. The principles of WF are the following: rates of




Fig. 1. An example of a feasible rate set and water-filling. On the left, a network of 3 links is given. Flow  $x_1$  connects  $S_1$  and  $D$  and flow  $x_2$  connects  $S_2$  and  $D$ . The set of feasible rates  $(x_1, x_2)$  is given on the right ( $c_1 = 7$ ,  $c_2 = 3$ ,  $c_3 = 8$ ). The water-filling [7], is depicted by the bold arrow. The max-min fair rate allocation is  $(5, 3)$ .

all flows are increased at the same pace, until one or more links are saturated. The rates of flows passing over saturated links are then frozen, and the other flows continue to increase rates. The algorithm is repeated until all rates are frozen. A more precise description of WF algorithm is given in Section III-B. It is proven in [7] that the output of WF, applied on a wired network, yields max-min fair allocation.

A simple example of WF in two dimensions on a wired network with single-path routing is given in Figure 1. We see in the example that although WF, as defined in [7], is related to the network topology, max-min fair allocation itself is solely a property of the set of feasible rates.

An extension of this scenario is introduced, for example, in [12] and [27]. Each flow is separately guaranteed a minimal rate. The algorithm used in [12] and [27] for computing the max-min fair rate allocation is a modified WF. Specifically, all rates are set to their minimal guaranteed values, and only the lowest rates are increased. A simple 2-dimensional example with an illustration of WF is given on the left of Figure 2.

Max-min fairness for single-rate multicast sessions is defined in [10]. This is generalized to multi-rate multicast sessions in [8]. Rates are again upper-bounded by links' capacities, and here we are interested in max-min fair allocation of receivers rates. A set of feasible allocations is linearly constrained, and a WF approach can be used. The geometric shape of the feasible set is essentially the same as in single-path routing.

The aforementioned scenarios have in common that the linearity of the constraints defining the feasible set. In [28], a single-path routing scenario is considered, and each source is assigned a utility, which is an increasing and concave function of its rate. Instead of searching for a max-min fair rate




Fig. 2. More examples of feasible rate sets. We consider the topology given on the left of Figure 1. We first assume there are minimum rates,  $m_1 = 0.5$  and  $m_2 = 1$ , for flows  $x_1$  and  $x_2$  respectively. The feasible set for this case is depicted on the left. The water-filling [12], [27] is represented with the bold arrow. On the right we consider utility max-min fairness as defined in [28], [8], on the network from Figure 1. The utility function is  $U(x) = x^2$ . The set of feasible utilities (non-convex set) is depicted on the right and the water-filling is represented with the bold arrow.

allocation, the authors of [28] look for max-min fair utility allocation. This approach is generalized in [8], where a max-min fair utility allocation is considered in the context of a multicast network. Here, the authors only required that a utility function be a strictly increasing but not necessarily concave function of rate, hence the feasible set is not necessarily convex. A simple 2-dimensional example is given in the right hand side of Figure 2. The WF algorithm can be used in this case as well.

#### D. When Bottleneck and Water-Filling Become Less Obvious

It is not always obvious how to generalize the notion of a bottleneck link and the water-filling approach to an arbitrary problem. To see why, consider a point-to-point multi-path routing scenario, where, to our knowledge, max-min fairness was not studied before. We look at the same set-up as above, but now allow for multiple paths to be used by a single source-destination pair. The end-to-end rate of communication between a source and a destination is equal to the sum of the rates over all used paths. An example is given in Figure 3: when node 1 talks to node 4, it transmit using the direct path over link 1-4 and in parallel it can relay through node 3. The end-to-end rate of communication between 1 and 4 equals to the sum of rates over paths 1-4 and 1-3-4. We are interested in a max-min fair rate allocation of end-to-end source-destination rates.

In the example in Figure 3, if we increase all the rates at the same pace, we will have rates of all paths equal to  $1/2$  when link 3-4 saturates. Now, if we continue increasing the rate over path 1-4, the rate of source-destination pair 1 will be higher than the rate of source destination 2, and path 2-3-4 will loose its bottleneck since it is no longer the




Fig. 3. A simple multi-path example. Top-left:  $S_1$  sends to  $D_1$  over two paths, 1-3-4 and 1-4, while  $S_2$  sends to  $D_2$  over a single path 2-3-4. All links have capacity 1. Right: the set of feasible rates. Bottom-left: the corresponding virtual single path problem.

biggest end-to-end flow that uses 3-4. If we change the previous definition of the bottleneck given in Section I-C, and instead of taking the biggest end-to-end flow, we consider the path with the highest rate, we obtain the max-min fair path rate allocation that differs from the end-to-end max-min fair rate allocation.

A first question that arises is how to define a bottleneck, such that the water-filling algorithm finds the max-min fair end-to-end rate allocation, if it is possible at all. Also, it is not clear if for a given definition of a bottleneck we can still claim that if each path has a bottleneck, the allocation is max-min fair. Finally, we do not even know, using the existing state of the art, if the max-min fair end-to-end rate allocation exists on an arbitrary multi-path network.

This example can be solved by observing that the max-min fair allocation depends only on the set of feasible rates. Consider again the example in Figure 3, top left. Call  $x_1 = y_1 + y_2$  the rate of source 1, and  $x_2$  the rate of source 2, where  $y_1$  is the rate of source 1 on path 1-4, and  $y_2$  on path 1-3-4. The set of feasible rates is the set of  $(x_1 \geq 0, x_2 \geq 0)$  such that there exist slack variables  $y_1 \geq 0, y_2 \geq 0$  with  $y_1 \leq 1, y_2 + x_2 \leq 1$  and  $x_1 = y_1 + y_2$ . This is an *implicit* definition, which can be made explicit by eliminating the slack variables; this gives the conditions  $x_1 \leq 1, x_1 + x_2 \leq 2$  (Figure 3, right). The set is convex, with a linear boundary, as in Figure 1, left. We can re-interpret the original multi-path problem as a virtual single path problem (Figure 3, bottom left), and apply the existing WF algorithms. On the virtual single-path problem we can define bottlenecks in a usual way. Note however that the concept of bottleneck in the virtual single path problem has lost its physical interpretation on the original problem.




Fig. 4. When water-filling does not work - consider the network topology on the left ( $c_1 = 7, c_2 = 3, c_3 = 8$ ). Suppose that node  $D$  receives parts of the same stream from both  $S_1$  and  $S_2$ , through flows  $x_1$  and  $x_2$ , and suppose it needs a minimal total rate of  $x_1 + x_2 \geq 7$ . We want to minimize loads of servers  $S_1$  and  $S_2$ , and we are interested in min-max fair allocation of  $(x_1, x_2)$ . The feasible rates set is given on the right. Min-max fair allocation exists, and it is  $(4, 3)$ .

### E. When Bottleneck and Water-Filling Do Not Work

Unfortunately, the approach with a virtual bottleneck does not always work. Consider the following workload distribution example: servers in a peer-to-peer network send data to a client; every client receives data from multiple servers, and has a guaranteed minimal rate of reception. Each flow from a server to a client is constrained by link capacities. Our goal is to equalize load on the servers while satisfying the capacity constraints.

A natural definition of fairness in this setting is min-max fairness, where we try to give the least possible work to the most loaded server. We say that a load on the servers is min-max fair if we cannot decrease a load on a server without increasing a load of another server that already has a higher load. A 2-dimensional example is given and explained in Figure 4. One can verify that it is not possible to define a virtual bottleneck in this case. We discuss this example in more detail in Section III-B.2 and Section IV-A.

A similar, but simpler, example is given in [14], which focuses on finding a leximax minimal allocation (we show in Section III that the leximax minimal allocation obtained in [14] is in fact min-max fair). Its complexity is of the order of  $N$  polynomial steps in  $\mathbb{R}^N$ , in the case where the feasible set is defined by linear constraints.

In Section IV-B we present another example where water-filling does not work. We consider the lifetime of nodes in a sensor network, inspired by the example introduced in [13], which studied the minimum lifetime. The lifetime of a node is a time until a node exhausts its battery, and it depends on the routing policy of a network. Unlike in [13], we study the routing strategy that achieves the min-max

fair allocation of lifetimes of nodes. We characterize the set of lifetimes that can be achieved with any possible routing strategy, and we show that the min-max fair lifetime allocation exists. However, as we also show, it is not possible to obtain it by water-filling.

### F. Our Findings

Our first finding is on the existence of max-min fairness. We give a large class of continuous sets on which a max-min fair allocation does exist, and we theoretically prove the existence. This class contains, but is not limited to, all compact, convex subsets of an arbitrary dimension Euclidean space  $\mathbb{R}^N$ . We also illustrate in a few examples that there are sets on which max-min fairness does not exist, thus that our result is not trivial.

Our second finding is on algorithms to locate the max-min fair allocation. In Section III, we give a general purpose, centralized algorithm, called *Max-min Programming (MP)*, and prove that it finds the max-min fair allocation in all cases where it exists. Its complexity is of the order of  $N$  linear programming steps in  $\mathbb{R}^N$ , in general, whenever the feasible set is defined by linear constraints.

The third finding is on the relation between the general MP algorithm and the existing WF algorithm. We recall the definition of the free disposal property and show that, whenever it holds, Max-min programming (MP) degenerates to the simpler Water-filling (WF) algorithm (originally defined in [7]), whose complexity is much lower. The free-disposal property corresponds to cases where a bottleneck argument can be made, all previously known centralized algorithms for such cases rely on the water-filling approach. We note that WF requires the feasible set to be given in explicit form, unlike MP, and we discuss the case of an implicit feasible set with the free-disposal property.

We use a novel approach to analyze properties of max-min fairness. Instead of considering a specific networking problem with an underlying network topology, we focus only on the feasible rate sets. Therefore, our framework does not depend on a specific problem; it is general and it unifies the existing approaches that analyze max-min fairness.

In Section IV we show applications of the results for two networking examples. We give specific, numerical examples where the min-max fair allocation exists, but the feasible sets do not have the

free-disposal property, hence a classical water-filling cannot be used. We show in these examples how MP does find max-min fair allocation even when the free-disposal does not hold. This way, we verify that our framework unifies previous results, and extends the applicability of max-min fairness to new scenarios. For additional examples, see [20].

All our results are given for max-min fairness; they apply mutatis mutandis to min-max fairness. They are valid for weighted and unweighted max-min and min-max fairness, using the transformation given in Section II-A. Distributed algorithms for the computation of max-min fair allocations [9], [1] are left outside the scope of this paper.

### G. Organization of The Paper

In Section II we define our framework (max-min and min-max fairness in  $N$  continuous variables). We mention a number of elementary results, such as the uniqueness and the reduction of weighted max-min fairness to the unweighted case. We recall the definition of leximin ordering that we use in a latter analysis. We prove our first main result about the existence of max-min fairness. In Section III, we give the definitions of the two analyzed algorithms: Max-min Programming (MP) and Water-filling (WF), and we discuss the other two main findings. In Section IV we illustrate our framework on two networking examples. We conclude in Section V. Proofs are in the appendix. An extended version of this paper can be found in [20].

## II. MAX-MIN AND MIN-MAX FAIRNESS IN EUCLIDEAN SPACES

In this section we provide a precise definition of max-min and min-max fairness and give results on their existence.

### A. Definitions and Uniqueness

Consider a set  $\mathcal{X} \subset \mathbb{R}^N$ . We define the max-min and min-max fair vectors with respect to set  $\mathcal{X}$  as follows:

*Definition 1:* [7] A vector  $\vec{x}$  is “max-min fair on set  $\mathcal{X}$ ” if and only if for all  $\vec{y} \in \mathcal{X}$  such that there exists  $s \in \{1, \dots, N\}$ ,  $y_s > x_s$ , there exists  $t \in \{1, \dots, N\}$  such that  $y_t < x_t \leq x_s$ . In other words, increasing some component  $x_s$  must be at the expense of decreasing some already smaller or equal component  $x_t$ .

*Definition 2:* A vector  $\vec{x}$  is “min-max fair on set  $\mathcal{X}$ ” if and only if for all  $\vec{y} \in \mathcal{X}$  such that there exists  $s \in \{1, \dots, N\}$ ,  $y_s < x_s$ , then there exists  $t \in \{1, \dots, N\}$  such that  $y_t > x_t \geq x_s$ . In other words decreasing some component  $x_s$  must be at the expense of increasing some already larger component  $x_t$ .

It is easy to verify that if  $\vec{x}$  is a min-max fair vector on  $\mathcal{X}$ , then  $-\vec{x}$  is max-min fair on  $-\mathcal{X}$  and vice versa. Thus, in the remainder of the paper, we give theoretical results only for max-min fairness, and the results for min-max follow directly.

Uniqueness of max-min fairness is assured by the following proposition:

*Proposition 1:* [7] If a max-min fair vector exists on a set  $\mathcal{X}$ , then it is unique.

The proof of the proposition is given in [7].

Weighted min-max fairness is a classical variation of max-min fairness, defined as follows. Given some positive constants  $w_i$  (called the “weights”), a vector  $\vec{x}$  is “weighted-max-min fair” on set  $\mathcal{X}$ , if and only if increasing one component  $x_s$  must be at the expense of decreasing some other component  $x_t$  such that  $x_t/w_t \leq x_s/w_s$  [7]. This is generalized in [8], which introduces the concept of “util max-min fairness”: given  $N$  increasing functions  $\phi_i : \mathbb{R} \rightarrow \mathbb{R}$ , interpreted as utility functions, a vector  $\vec{x}$  is “util-max-min fair” on set  $\mathcal{X}$  if and only if increasing one component  $x_s$  must be at the expense of decreasing some other component  $x_t$  such that  $\phi_t(x_t) \leq \phi_s(x_s)$  (this is also called “weighted max-min fairness” in [17]). Consider the mapping  $\phi$  defined by

$$(x_1, \dots, x_N) \rightarrow (\phi_1(x_1), \dots, \phi_N(x_N)) \quad (1)$$

It follows immediately that a vector  $\vec{x}$  is util-max-min fair on set  $\mathcal{X}$  if and only if  $\phi(\vec{x})$  is max-min fair on the set  $\phi(\mathcal{X})$ , the case of weighted max-min fairness corresponding to  $\phi_i(x_i) = x_i/w_i$ . Thus, we now restrict our attention to unweighted max-min fairness.

### B. Max-Min Fairness and Leximin Ordering

In the rest of our paper we will extensively use leximin ordering, a concept we borrow from economics, and which we now recall. Let us define the “order mapping”  $\mathcal{T} : \mathbb{R}^N \rightarrow \mathbb{R}^N$  as the mapping that sorts  $\vec{x}$  in non-decreasing order, that is:  $\mathcal{T}(x_1, \dots, x_n) = (x_{(1)}, \dots, x_{(n)})$ , with  $x_{(1)} \leq x_{(2)} \leq \dots \leq x_{(n)}$  and for all  $i$ ,  $x_{(i)}$  is one of the  $x_j$ s. Let us also define the lexicographic ordering of vectors

in  $\mathcal{X}$  by  $\vec{x} \stackrel{lex}{>} \vec{y}$  if and only if  $(\exists i) x_i > y_i$  and  $(\forall j < i) x_j = y_j$ . We also say that  $\vec{x} \stackrel{lex}{\geq} \vec{y}$  if and only if  $\vec{x} \stackrel{lex}{>} \vec{y}$  or  $\vec{x} = \vec{y}$ . This latter relation is a total order on  $\mathbb{R}^N$ .

*Definition 3:* [2] Vector  $\vec{x}$  is *leximin larger* than or equal to  $\vec{y}$  if  $\mathcal{T}(\vec{x}) \stackrel{lex}{\geq} \mathcal{T}(\vec{y})$ .

*Definition 4:* [2] Vector  $\vec{x} \in \mathcal{X}$  is *leximin maximal* on a set  $\mathcal{X}$  if for all  $\vec{y} \in \mathcal{X}$  we have  $\mathcal{T}(\vec{x}) \stackrel{lex}{\geq} \mathcal{T}(\vec{y})$ .

Note that a leximin maximum is not necessarily unique. See Figure 5 on the left for a counter-example.

*Proposition 2:* [23] Any compact subset of  $\mathbb{R}^n$  has a leximin maximal vector.

It has been observed in [28], [12], [8] that a max-min fair allocation is also leximin maximal, for the feasible sets defined in these papers. It is generalized to an arbitrary feasible set in [23], as follows.

*Proposition 3:* [23] If a max-min fair vector exists on a set  $\mathcal{X}$ , then it is the unique leximin maximal vector on  $\mathcal{X}$ .

Thus, the existence of a max-min fair vector implies the uniqueness of a leximin maximum. The converse is not true: see Figure 5, right, for an example of a set with unique leximin maximal vector which is not max-min achievable. [23] defines a weaker version of max-min fairness, “maximal fairness”; it corresponds to the notion of leximin maximal vector, hence it is not unique, and exists on a larger class of feasible sets. We leave this weaker version outside the scope of this paper.

It is shown in [2] that if a vector is leximin maximal, it is also Pareto optimal. Therefore, from Proposition 3 it follows that the max-min fair vector, if it exists, is Pareto optimal. The converse is not necessarily true.

### C. Existence and Max-Min Achievable Sets

As already mentioned, a number of papers showed the existence of max-min fair allocation in many cases, using different methods. We give here a generalized proof that holds on a larger class of continuous sets that incorporates, but is not limited to convex sets. This class of continuous sets includes the feasible sets of all the networking applications we are aware of. Note that a max-min fair vector does not exist on all feasible sets, even sets that are compact and connected. Simple counter-examples




Fig. 5. Examples of 2-dimensional sets that do not have max-min fair allocation. Point (1, 3) is not max-min fair in the example on the left since there exists point (3, 1) that contradicts with definition Definition 1. Both points (1, 3) and (3, 1) are leximin maximal in this example. In the example on the right, point (3, 1) is the single leximin maximal point. Still, it is not the max-min fair point. Note that there exist no real networking example we are aware of that has these feasible rate sets – these sets are only artificial examples that illustrate properties of leximin ordering.

are given in Figure 5. However, these counter-examples are hand-crafted and do not correspond to any networking scenario. In the remainder of this section we give a sufficient condition for the existence of a max-min vector.

*Definition 5:* A set  $\mathcal{X}$  is max-min achievable if there exists a max-min fair vector on  $\mathcal{X}$ .

*Theorem 1:* Consider a mapping  $\phi$  defined as in Equation 1. Assume that  $\phi_i$  is increasing and continuous for all  $i$ . If the set  $\mathcal{X}$  is convex and compact, then  $\phi(\mathcal{X})$  is max-min achievable.

The proof is in the appendix. As a special case, obtained by letting  $\phi_i(x) = x$ , we conclude that all convex and compact sets are max-min achievable. Taking  $\phi_i(x) = x/w_i$ , we also conclude that weighted max-min fairness exists on all compact, convex sets. More generally, util-max-min fairness exists on all compact, convex sets, if the utility functions are continuous (and increasing).

In [28], the utility functions  $\phi_i$  are arbitrary, continuous, increasing and concave functions. With these assumptions, the set  $\phi(\mathcal{X})$  is also convex and compact. Note that in general, though, the set  $\phi(\mathcal{X})$  used in Theorem 1 is not necessarily convex. Examples with non-convex sets are provided in [17] and [8].

## III. MAX-MIN PROGRAMMING AND WATER-FILLING

In the following section present the max-min programming (MP) algorithm, which finds the max-min fair vector on any feasible set, if it exists. We also define a condition called a free-disposal property, and show that, under that conditions, a commonly used water-filling (WF) algorithm coincides with the

MP algorithm, and is guaranteed to find the max-min fair allocation.

#### A. The Max-Min Programming (MP) Algorithm

The idea of the MP algorithm is first to find the smallest component of the max-min fair vector, which is done by maximizing the minimal coordinate. Once this is done, the minimal coordinate is fixed, and the dimension corresponding to the minimal coordinate is removed. This step is repeated until all coordinates are fixed, and we show that a vector obtained in such way is indeed the max-min fair one. A precise definition of the algorithm is given below.

1. let  $S^0 = \{1, \dots, N\}, \mathcal{X}^0 = \mathcal{X}, \mathcal{R}^0 = \mathcal{X}, n = 0$
2. **do**
3.  $n = n + 1$
4. Problem  $MP^n$ : maximize  $T^n$  subject to:
 
$$\begin{cases} (\forall i \in S^{n-1}) & x_i \geq T^n \\ \text{for some } \vec{x} \in \mathcal{X}^{n-1} \end{cases}$$
5. let  $\mathcal{X}^n = \{\vec{x} \in \mathcal{X}^{n-1} \mid (\forall i \in S^{n-1}) x_i \geq T^n, (\exists i \in S^{n-1}) x_i > T^n\}$ ,  
 $\mathcal{R}^n = \{\vec{x} \in \mathcal{X}^{n-1} \mid (\forall i \in S^{n-1}) x_i \geq T^n\}$   
 and  $S^n = \{i \in \{1 \dots N\} \mid (\forall \vec{x} \in \mathcal{X}^n) x_i > T^n\}$
6. **until**  $S^n = \emptyset$
7. return the only element in  $\mathcal{R}^n$

The algorithm maximizes in each step the minimal coordinate of the feasible vector, until all coordinates are processed. The  $n$ -th step of the algorithm is a minimization problem, called  $MP^n$ , where  $\mathcal{X}^n$  represents the remaining search space,  $S^n$  represents the direction of search, in terms of coordinates that can be further increased, and  $\mathcal{R}^n$  is the set that will, in the end, contain a single rate allocation, the max-min fair one.

1) *Proof of Correctness*: The algorithm always terminates if  $\mathcal{X}$  is compact and max-min achievable, and  $\mathcal{X}^n$  is reduced to one single element, which is the required max-min fair vector, as is proved in the following theorem:

*Theorem 2*: If  $\mathcal{X}$  is compact and max-min achievable, the above algorithm terminates and finds the max-min fair vector on  $\mathcal{X}$  in at most  $N$  steps.

The proof is in the appendix. Note that the theorem requires set  $\mathcal{X}$  to be compact but this usually just a technical assumption since in most of the practical examples the feasible sets are compact.

The algorithm presented in [14] for calculating the leximax minimal allocation is a particular implementation of MP. In each step, this algorithm maximizes the minimum rate of links, which is exactly step 4 of the MP algorithm, tailored to the problem considered. The overall complexity of the algorithm in [14] is thus the same as the complexity of MP. Since the feasible set considered there is compact convex, it follows from Theorem 1 and Proposition 3 that the leximax minimal allocation obtained in [14] is in fact a min-max fair allocation.

2) *Numerical Examples*: In order to illustrate the behaviour of MP, we consider two simple examples. The first one is the network from Figure 1. The set of feasible rates is

$$\mathcal{X} = \{(x_1, x_2) \mid 0 \leq x_1 \leq 7, 0 \leq x_2 \leq 3, x_1 + x_2 \leq 8\}, \quad (2)$$

and it is depicted on the right of Figure 1. We are looking for the max-min fair rate allocation.

In the first step of the algorithm we have  $\mathcal{X}^0 = \mathcal{X}, \mathcal{R}^0 = \mathcal{X}, S^0 = \{1, 2\}$ . By solving the linear program in step 4, we obtain  $T^1 = 3$ . We further have  $\mathcal{X}^1 = \{(x_1, 3) \mid 3 < x_1 \leq 5\}, \mathcal{R}^1 = \{(x_1, 3) \mid 3 \leq x_1 \leq 5\}, S^1 = \{1\}$ . Again by solving the linear program in step 4 we obtain  $T^2 = 5$ . Now we have  $\mathcal{X}^2 = \emptyset, \mathcal{R}^2 = \{(5, 3)\}, S^2 = \emptyset$ . The algorithm terminates and set  $\mathcal{R}^2$  contains only the max-min fair rate allocation.

The second example we consider is the load distribution example from Figure 4. The set of feasible rates is

$$\mathcal{X} = \{(x_1, x_2) \mid 0 \leq x_1 \leq 7, 0 \leq x_2 \leq 3, 7 \leq x_1 + x_2 \leq 8\}, \quad (3)$$

and it is depicted on the right of Figure 4. We are looking for the min-max fair rate allocation on set  $\mathcal{X}$ , which is equivalent of finding max-min fair rate allocation on set  $-\mathcal{X}$ , as discussed in Section II-A.

In the first step of the algorithm we have  $\mathcal{X}^0 = -\mathcal{X}, \mathcal{R}^0 = -\mathcal{X}, S^0 = \{-1, -2\}$ . By solving the linear program in step 4 we obtain  $T^1 = -4$ . We then have  $\mathcal{X}^1 = \{(-4, -3)\}, \mathcal{R}^1 = \{(-4, -3)\}, S^1 = \emptyset$ . The algorithm terminates and set  $\mathcal{R}^2$  contains a single allocation which. The min-max fair rate allocation is thus  $(4, 3)$ .

Note that when the max-min fair allocation does not exist, MP will not give one of the leximin maximal points, as one might expect. To see this, consider the examples from Figure 5. In both examples, in the first step of MP, we will have  $T^1 = 1$  and  $S^1 = \emptyset$ , and the algorithm will return  $(1, 1)$

as the optimal point. This point is neither leximin maximal, nor Pareto optimal.

Before applying MP to a specific class of problems, it is thus important to verify, e.g. using results from Section II, that max-min fairness exists. This has to be done only once, since the existence of max-min fairness depends on the nature of the problem. Once the existence is verified, the MP algorithm can be further applied on any instance of the problem and will always yield the correct result.

### B. The Water-Filling (WF) Algorithm

We now compare MP with the water-filling approach used in the traditional setting [7]. We here present a generalized version that includes minimal rate guarantees, as in [27].

We first introduce the concept of free disposal property. It is defined in economics as the right of each user to dispose of an arbitrary amount of owned commodities [2], or alternatively, to consume fewer resources than maximally allowed. We then modify it slightly, as follows. Call  $\vec{e}_i$  a unitary vector  $(\vec{e}_i)_j = \delta_{ij}$ .

*Definition 6:* We say that a set  $\mathcal{X}$  has the free-disposal property if (1) there exists  $\vec{m}$  with  $x_i \geq m_i$  for all  $\vec{x} \in \mathcal{X}$  and (2) for all  $i \in \{1, \dots, N\}$  and for all  $\alpha$  such that  $\vec{x} - \alpha \vec{e}_i \geq \vec{m}$ , we have  $\vec{x} - \alpha \vec{e}_i \in \mathcal{X}$ .

Informally, free disposal applies to sets where each coordinate is independently lower-bounded, and requires that we can always decrease a feasible vector, as long as we remain above the lower bounds. We now describe the Water-Filling algorithm.

0. Assume  $\mathcal{X}$  is free-disposal
1. let  $S^0 = \{1, \dots, N\}$ ,  $\mathcal{X}^0 = \mathcal{X}$ ,  $\mathcal{R}^0 = \mathcal{R}$ ,  $n = 0$
2. **do**
3.  $n = n + 1$
4. Problem  $WF^n$ : maximize  $T^n$  subject to:
 
$$\begin{cases} (\forall i \in S^{n-1}) x_i = \max(T^n, m_i) \\ \text{for some } \vec{x} \in \mathcal{X}^{n-1} \end{cases}$$
5. let  $\mathcal{X}^n = \{\vec{x} \in \mathcal{X}^{n-1} \mid (\forall i \in S^{n-1}) x_i \geq T^n, (\exists i \in S^{n-1}) x_i > T^n\}$ ,  
 $\mathcal{R}^n = \{\vec{x} \in \mathcal{X}^{n-1} \mid (\forall i \in S^{n-1}) x_i \geq T^n\}$   
 and  $S^n = \{i \in \{1 \dots N\} \mid (\forall \vec{x} \in \mathcal{X}^n) x_i > T^n\}$
6. **until**  $S^n = \emptyset$
7. return the only element in  $\mathcal{X}^n$

1) *Equivalence of WF and MP:* The following theorem demonstrates the equivalence of MP and WF on free-disposal sets.

*Theorem 3:* Let  $\mathcal{X}$  be a max-min achievable set that satisfies the free-disposal property. Then, at every step  $n$ , the solutions to problems  $WF^n$  and  $MP^n$  are the same.

The proof is in the appendix. Thus, under the conditions of the theorem, WF terminates and returns the same result as MP, namely the max-min fair vector if it exists. The theorem is actually stronger, since the two algorithms provide the same result at every step. However, if the free-disposal property does not hold, then WF may not compute the max-min fair allocation. We refer to Section III-B.2 for such an example.

The examples previously mentioned of single path unicast routing [7], multicast util-max-min fairness [10], [8] and minimal rate guarantee [27], [12] all have the free-disposal property. Thus, the water-filling algorithm can be used, as is done in all the mentioned references. In contrast, the load distribution example [14] is not free-disposal, and all we can do is use MP, as is done in [14] in a specific example.

The multi-path routing example also has the free-disposal property, but the feasible set is defined implicitly. We discuss the implications of this in the next section.

2) *Numerical Examples:* To illustrate the behaviour of WF, we consider again the same two examples as in Section III-A.2. In the first example, depicted in Figure 4, the feasible rate set, described by (2), has the free-disposal property. It is easy to verify that sets  $\{\mathcal{X}^i\}_{i=1 \dots 3}$ ,  $\{\mathcal{R}^i\}_{i=1 \dots 3}$ ,  $\{S^i\}_{i=1 \dots 3}$  are taking exactly the same values as in the case of MP, described in Section III-A.2. This confirms the findings of Theorem 3.

The second example we consider is the load distribution example depicted in Figure 4 and described by (2). For this type of problem we cannot a priori set the upper limits in  $\vec{m}$ , as [12], [27], as they are not universal (they would need to depend on given network topology and are not known in advance). Then, it is easy to verify that the linear program in step 4 (with minimization instead of maximization since we are looking for min-max fairness) has no solution. Therefore, in this case, WF cannot find the min-max fair rate allocation.

Note that the free-disposal property is a sufficient but not a necessary condition for MP to degenerate to WF. This becomes evident when considering again the example from Figure 4. Suppose that  $c_1 =$



3,  $c_2 = 3$ ,  $c_3 = 4$ , and, in addition, the minimum rate constraint is  $x_1 + x_2 \geq 3$ . The feasible rate set in this example has the same shape and orientation as in Figure 4, but it is translated to the left such that it touches both  $x_1$  and  $x_2$  axes. In this particular example, it is easy to verify that the set still does not have the free-disposal property. However WF finds the min-max allocation in a single step.

### C. Complexity Of The Algorithms In Case Of Linear Constraints

Let us now assume that  $\mathcal{X}$  is an  $n$ -dimensional feasible set defined by  $m$  linear inequalities. Each of the  $n$  steps of the MP algorithm is a linear programming problem, hence the overall complexity is  $O(nLP(n, m))$ , where  $LP(n, m)$  is the complexity of linear programming. The WF algorithm also has  $n$  steps, each of complexity  $O(m)$  (since in step 4 we have to find the maximum value of  $T$  that satisfies the equality in each of the  $m$  inequalities, and take as the result the smallest of those). Hence the complexity of WF is  $O(nm)$ . Linear programming has solutions of exponential complexity in the worst case, however in most practical cases there are solutions with polynomial complexity.

Assume next that  $\mathcal{X}$  is defined implicitly, with an  $l$ -dimensional slack variable (for an example scenario, see multi-path case on Figure 3). We can use MP, which works on implicit sets, resulting in complexity  $O(nLP(n, m))$ . If the set is free-disposal, we can also use WF, but we need to find an explicit characterization of the feasible set. In most cases, finding an explicit characterization of the feasible set can be done in polynomial time. To see that, consider again the example from Figure 3. The slack variables represent rates of different paths, whereas we are interested only in the end-to-end rates. Finding a set of feasible end-to-end rates is equivalent to a well known problem of finding maximum flows in a network [24] (see [14] for an example in the networking context). As shown in [24], this is a problem of a polynomial complexity. Note that it might be possible to construct an implicitly defined feasible set that cannot be converted to an explicit form in a polynomial time. However, we are not aware of any existing example of such a set. A further analysis is out of the scope of our paper.

Once we have an explicit characterization, the remaining complexity of WF is still  $O(mn)$ . In

practical applications, we are likely to be interested in explicitly finding the values of the slack variables at the max-min fair vector. Finding these values is a linear program. Here, it is sufficient to make the set explicit only once for a given problem. We conclude that in many practical problems, it is likely to be faster to make the set of constraints explicit and use WF rather than MP.

## IV. EXAMPLE SCENARIOS

In this section we provide two examples that arise in a networking context, which were not previously studied, and to which our theory applies. The examples are taken from problems that occur in P2P and wireless sensor networks, respectively. We show that in these two scenarios the feasible sets do not have the free-disposal property. We illustrate on simple but detailed numerical examples that WF does not work, whereas MP gives a correct result. For additional examples, see [20].

### A. Load Distribution In P2P Systems

Let us consider a peer-to-peer network, where several servers can supply a single user with parts of a single data stream (e.g. by using Tornado codes [11]). There is a minimal rate a user needs to achieve, and there is an upper bound on each flow given by a network topology and link capacities.

Let  $\vec{x}$  be the total loads on the servers,  $\vec{y}$  the flows from the servers to clients,  $\vec{z}$  the total traffic received by clients,  $\vec{c}$  the capacities of links and  $\vec{m}$  the minimum required rates of the flows. We can then represent the feasible rate set as

$$\mathcal{X} = \{ \vec{x} : (\exists \vec{y}, \vec{z}) \begin{aligned} A\vec{y} &\leq \vec{c}, \\ B\vec{y} &= \vec{x}, C\vec{y} = \vec{z}, \vec{z} \geq \vec{m} \end{aligned} \}, \quad (4)$$

where  $A, B, C \geq 0$  are arbitrary matrices defined by network topology and routing.

A simple example depicted in Figure 4. Client  $D$  receives data from both servers  $S_1$  and  $S_2$  and it wants minimal guaranteed rate  $m$ . There is flow  $y_1$  going from  $S_1$  to  $D$  over links 1 and 3, and flow  $y_2$  going from  $S_2$  to  $D$  over links 2 and 3. We have that the total egress traffic of  $S_1$  is  $x_1 = y_1$ , and of  $S_2$  is  $x_2 = y_2$ . The total ingress traffic of  $D$  is  $z_1 = y_1 + y_2$ . We thus have the following matrices

$$A = \begin{bmatrix} 1 & 0 \\ 0 & 1 \\ 1 & 1 \end{bmatrix}, B = \begin{bmatrix} 1 & 0 \\ 0 & 1 \end{bmatrix}, C = [ 1 \quad 1 ],$$

that define the constraint set, visualized in Figure 4.

In a peer-to-peer scenario, each server is interested in minimizing its own load, hence it is natural to look for the min-max fair vector on set  $\mathcal{X}$ , which minimizes loads on highly loaded servers.

Since set  $\mathcal{X}$  is convex, it is min-max achievable. Since it does not have the free-disposal property in general, WF is not applicable. This is shown in Section III-B.2 on a simple example. Min-max fair allocation can be found by means of the MP algorithm. This is illustrated on the example in Section III-A.2.

Note that this form of a feasible set is unique in that it introduces both upper and lower bounds on a sum of components of  $\vec{x}$  and, as such, is more general than the feasible sets in the above presented examples, such as [14].

### B. Maximum Lifetime Sensor Networks

In this section we consider a sensor network example, and we want to minimize the average transmitting powers of sensors. This example motivated by [13], [22]. We assume a network has a certain minimal amount of data to convey to a sink, and we consider different scheduling and routing strategies that achieve this goal. Each of these strategies yields different average power consumptions, and we look for min-max fair vector of average power consumptions of sensors. We suppose that the network is built on the top of the ultra-wide band physical layer described in [25], or low power, low processing gain CDMA physical layer, described in [6].

Consider a set of  $n = \{1 \cdots N\}$  nodes, some of which are sensors and some are sinks. We assume sensors feed data to sinks over the network, and can do so by sending directly, or relaying over other sensors or sinks. When node  $s$  sends data to node  $d$ , it does so using some transmission power  $P_s$ . The signal attenuates while propagating through space, and is received at  $d$  with power  $P_s h_{sd}$ , where  $h_{sd}$  is an arbitrary positive number, referred to as the attenuation between  $s$  and  $d$ .

Receiver  $d$  tries to decode the information sent by  $s$  in presence of noise and interference. If  $N$  denotes the white background noise, than the total interference experienced by  $D$  is  $I = N + \sum_{i \neq s} P_i h_{id}$ . The maximum rate of information  $d$  can achieve is then [25], [6]

$$x_{sd} = K \frac{P_s h_{sd}}{N + \sum_{i \neq s} P_i h_{id}}.$$

We also assume that a node can only send to or receive from one node at a time.

In addition, nodes can change their transmission power over time. We assume a slotted protocol, where in every slot  $t$ , every node  $s$  can choose an arbitrary transmission power  $P_s(t)$ . If  $s$  chooses not to transmit, it sets  $P_s(t) = 0$ . A succession of slots in time is called a schedule. Link  $sd$  achieves rate  $x_{sd}(t)$  where the rate depends on allocated powers, as explained above. We denote with  $\bar{x}_{sd}$  the average rate of link  $sd$  throughout a schedule. Let  $\bar{\mathbf{x}}$  be the vector of all  $\{\bar{x}_{sd}\}_{1 \leq s, d \leq N}$ . We denote by  $\mathcal{X}$  a set of feasible  $\bar{\mathbf{x}}$ , that is such that there exists a schedule and power allocations that achieve those rates. Similarly to the average rate, we can calculate the average power dissipated by a node during a schedule, which we denote by  $\bar{P}_s$ . We denote by  $\mathcal{P}(\bar{\mathbf{x}})$  a set of possible average power dissipations that achieve average rate  $\bar{\mathbf{x}}$ . Refer to [18] for a more detailed explanation of the model.

From the application point of view, we assume sensors measure the same type of information. Each of the several sinks needs to receive a certain rate of the information, regardless from what sensor it comes. Let us denote with  $R_d$  the total rate of information received by sink  $d$ . We then have a constraint  $R_d \leq M_d$ .

In order to define routing, we further introduce a concept of paths, similarly as in the previous example. Path  $p = \{1 \cdots P\}$  is a set of links. We say  $A_{l,p} = 1$  if link  $l = (s, d)$ , for some  $s, d$ , belongs to path  $p$ . Otherwise,  $a_{p,l} = 0$ . We also say  $B_{s,p} = 1$  and  $C_{s,p} = 1$  if node  $s$  is the starting or the finishing point of the path  $p$ , respectively. Let  $y_p$  be the average rate on path  $p$ .

The goal is to minimize the average power dissipations, under the above constraints. The set of feasible average power dissipations can be formally described as  $\mathcal{P} = \{\bar{\mathbf{p}} \mid (\exists \bar{\mathbf{x}} \in \mathcal{X}) \bar{\mathbf{p}} \in \mathcal{P}(\bar{\mathbf{x}}), \mathbf{A}\mathbf{y} \leq \bar{\mathbf{x}}, \mathbf{R} = \mathbf{C}\mathbf{y} \leq \mathbf{M}\}$ . We are interested in finding the min-max average power allocation over set  $\mathcal{P}$ .

This is a difficult optimization problem that has not been fully solved, and we do not intend to solve it here in its general form. Instead, we want to illustrate in a simple example from Figure 6, that the feasible set does not always have the free-disposal property, and furthermore that WF, as such, cannot be used.

In our simple example from Figure 6, we consider two sensors,  $S_1$  and  $S_2$ , and two sinks,  $D_1$  and  $D_2$ .




Fig. 6. Sensor example: On the left an example of a network with 2 sensors and 2 sinks is given. We let  $P^M = N = 1$ , and  $h_{S_1 D_1} = h_{S_1 D_2} = 1, h_{S_2 D_1} = 10, h_{S_2 D_2} = 0.7$ , and the lower bounds on rates are  $M_1 = 0.6, M_2 = 0.4$ . On the right, the set of feasible average power dissipations is given.

We have three links,  $(S_1, D_1), (S_2, D_1), (S_2, D_2)$ , and three paths that coincide with each link (we assume other links cannot be established due to for example a presence of a wall).

It is shown in [19] that in this type of network any average rate allocation can be achieved by using the following simple power allocation policy: when a node is transmitting, it does so with maximum power; otherwise it is silent. It follows that any possible schedule in the network can have four possible slots:

**Slot 1 of duration  $\alpha_1$ :** Only sensor  $S_1$  sends to sink  $D_1$  with full power  $P^M$  and  $S_2$  is silent.

**Slot 2 of duration  $\alpha_2$ :** Sensor  $S_1$  sends to  $D_1$  while  $S_2$  sends to  $D_2$ .

**Slot 3 of duration  $\alpha_3$ :** Only  $S_2$  sends to  $D_1$ .

**Slot 4 of duration  $\alpha_4$ :** Only  $S_2$  sends to  $D_2$ .

If we normalize the duration of the schedule, we have  $\alpha_1 + \alpha_2 + \alpha_3 + \alpha_4 = 1$ .

Under the above scheduling, we have the following average rates and average dissipated powers

$$R_1 = \alpha_1 \frac{P^M h_{S_1 D_1}}{N} + \alpha_2 \frac{P^M h_{S_1 D_1}}{N + P^M h_{S_2 D_1}} \quad (5)$$

$$+ \alpha_3 \frac{P^M h_{S_2 D_1}}{N}, \quad (6)$$

$$R_2 = \alpha_2 \frac{P^M h_{S_2 D_2}}{N + P^M h_{S_1 D_2}} + \alpha_4 \frac{P^M h_{S_2 D_2}}{N}, \quad (7)$$

$$\bar{P}_1 = (\alpha_1 + \alpha_2 + \alpha_3) P^M, \quad (8)$$

$$\bar{P}_2 = (\alpha_2 + \alpha_4) P^M. \quad (9)$$

The set of feasible average powers is thus  $\mathcal{X} = \{(\bar{P}_1, \bar{P}_2) \mid (\exists \alpha_1 \dots \alpha_4) \sum_{i=1}^4 \alpha_i = 1, R_1 \geq M_1, R_2 \geq M_2\}$ .

To obtain a numeric example, we set  $K = P^M = N = 1, h_{S_1 D_1} = h_{S_1 D_2} = 1, h_{S_2 D_1} = 10, h_{S_2 D_2} =$

0.7, and  $M_1 = 0.6, M_2 = 0.4$ . Setting these values in (6)-(9) and simplifying the constraints, we achieve the following set of inequalities that defines set  $\mathcal{X}$ :

$$\bar{P}_1 + \bar{P}_2 \geq 1,$$

$$\bar{P}_1 + \alpha_3 \leq 1,$$

$$7\bar{P}_1 + 14\alpha_3 + 1 \leq 7\bar{P}_2,$$

$$\bar{P}_1 + 110\alpha_3 - 3.4 \geq 10\bar{P}_2,$$

$$\bar{P}_1, \bar{P}_2, \alpha_3 \in [0, 1].$$

The set  $\mathcal{P}$  is depicted on the right of Figure 6. It is easy to verify that this set does not have the free-disposal property. We verify that the first step of WF algorithm has no solution, hence water filling does not give the min-max allocation. On the other hand, a single iteration of MP gives us the min-max allocation on the set  $\mathcal{X}$  which in this case is  $(0.38, 0.62)$ . We underline again that only due to the simplicity of the example, WF fails at the first step, and MP solves the problem in one step. In a more complex example WF might fail on any step whereas MP will again solve the problem. However, due to the simplicity of the presentation we give here only a 4 node example.

## V. CONCLUSION

We have given a general framework that unifies several results on max-min and min-max fairness encountered in networking examples. We have extended the framework to account for new examples arising in mobile and peer-to-peer scenarios. We have elucidated the role of bottleneck arguments in the water-filling algorithm, and explained the relation to the free-disposal property; we have shown that the bottleneck argument is not essential to the definition of max-min fairness, contrary to popular belief. However, when it holds, it allows us to use simpler algorithms. We have given a general purpose algorithm (MP) for computing the max-min fair vector whenever it exists, and showed that it degenerates to the classical water-filling algorithm, when free disposal property holds. The existence of a max-min fair vector is not always guaranteed, even on compact sets. We have found a class of compact sets on which max-min fairness does exist. The extension of the class to other useful cases (such as discrete sets [23]) remains to be studied. Finally, we have focused on centralized algorithms for calculating max-min and min-max fair allocations. It will be interesting to explore their distributed counterparts.

## APPENDIX

## A. Proof of Existence of MMF

We first give an intuition on how we shall prove the theorem. We consider vector  $\vec{x}$  that is leximin maximal on the set  $\phi(\mathcal{X})$ , and we want to prove that this is at the same time the max-min fair vector. The proof is done by contradiction. We assume that there exists a vector  $\vec{y}$  that violates the definition of max-min fairness of vector  $\vec{x}$ . We will then construct vector  $\vec{z}$  from  $\vec{x}$  and  $\vec{y}$  such that  $\vec{z}$  is leximin-larger than  $\vec{x}$ , which will lead to contradiction. Function  $\phi()$  is strictly increasing, hence there exists and inverse  $\phi^{-1}()$ , which is also strictly increasing. Although set  $\phi(\mathcal{X})$  is not convex, set  $\mathcal{X}$  is convex. Therefore, we will chose  $\alpha$  such that vector  $\vec{z}$ , constructed as  $\phi^{-1}(\vec{z}) = \alpha\phi^{-1}(\vec{x}) + (1 - \alpha)\phi^{-1}(\vec{y})$ , is leximin larger than  $\vec{x}$ .

**Proof of Theorem 1:** Let  $\vec{x} \in \phi(\mathcal{X})$  be a vector such that for all  $\vec{y} \in \phi(\mathcal{X})$  we have  $\mathcal{T}(\vec{x}) \stackrel{lex}{\geq} \mathcal{T}(\vec{y})$ . Such a vector exists according to proposition 2, since set  $\mathcal{X}$  is compact. In order to prove the theorem, we proceed by contradiction, assuming that there exist  $\vec{y}$  and an index  $s \in \{1, \dots, N\}$  such that  $y_s > x_s$  and for all  $t \in \{1, \dots, N\}$ ,  $x_t \leq x_s$  we have  $y_t \geq x_t$ . We then define a permutation  $\pi : \{1, \dots, N\} \rightarrow \{1, \dots, N\}$  such that for all  $i < j$ ,  $\vec{x}_{\pi(i)} \leq \vec{x}_{\pi(j)}$ , and either  $x_{\pi(l)} < x_{\pi(l+1)}$  or  $l = N$ , where  $l = \pi^{-1}(s)$ . The last part of the requirement is important if there are several components of the vector that are equal to  $x_s$ , hence there are several permutations that maintain non-decreasing ordering. We then want  $s$  to be mapped by  $\pi$  to the largest such index: if  $l = \pi^{-1}(s)$  then either  $x_s < x_{\pi(l+1)}$  or  $l$  is the last index ( $l = N$ ).

Next, let us define vector

$$\vec{z}(\alpha) = \phi(\alpha\phi^{-1}(\vec{x}) + (1 - \alpha)\phi^{-1}(\vec{y})). \quad (10)$$

Although we cannot make a convex combination of  $\vec{x}$  and  $\vec{y}$  since set  $\phi(\mathcal{X})$  is not convex, we can make a convex combination of  $\phi^{-1}(\vec{x})$  and  $\phi^{-1}(\vec{y})$  in the set  $\mathcal{X}$  which is convex.

For  $\alpha \in (0, 1)$ ,  $\vec{z}(\alpha)$  belongs to  $\phi(\mathcal{X})$  due to convexity of  $\mathcal{X}$ . From (10) we have for all  $\alpha \in (0, 1)$ ,  $i \in \{1, \dots, N\}$ ,  $\min(\phi^{-1}(x_i), \phi^{-1}(y_i)) < \phi^{-1}(\vec{z}(\alpha)_i) < \max(\phi^{-1}(x_i), \phi^{-1}(y_i))$ , hence  $\min(x_i, y_i) < \vec{z}(\alpha)_i < \max(x_i, y_i)$ , due to strictly increasing properties of functions  $\phi_i$  and  $\phi_i^{-1}$ . Also, for all  $i$  let us pick an arbitrary  $\alpha_i$  satisfying

$$\alpha_i \in \begin{cases} \left( \frac{\phi_i^{-1}(x_s) - \phi_i^{-1}(y_i)}{\phi_i^{-1}(x_i) - \phi_i^{-1}(y_i)}, 1 \right), & x_s \in [y_i, x_i), \\ [0, 1), & \text{otherwise} \end{cases}$$

and we call  $\alpha_m = \max_i(\alpha_i)$  and  $\vec{z} = \vec{z}(\alpha_m) \in \phi(\mathcal{X})$  (since  $\alpha_m \in [0, 1)$ ). Intuitively, if for some  $i$ ,  $y_i < x_s$ , we want to have  $z_i > x_s$ . If  $x_i \leq x_s$  (including when  $i = s$ ) we then by assumption have  $y_i \geq x_i$ , and we choose  $\alpha$  such that we get  $z_i > x_i$ . Finally, if both  $y_i > x_s$ ,  $x_i > x_s$ , then we can select any  $\alpha$  and we will have  $z_i > x_s$ .

We have chosen the highest of  $\alpha_i$ , hence we now have that if  $x_i \leq x_s$ , then  $z_i \geq x_i$ , otherwise  $z_i > x_s$ . We also have  $z_s > x_s$ . From this, we derive the property of the sorted vectors that  $z_{\pi(i)} \geq x_{\pi(i)}$  for  $i < l$ , and  $z_{\pi(i)} > x_{\pi(l)}$  for  $i \geq l$ .

We first notice that for all  $i$ ,  $z_{\pi(i)} \geq x_{\pi(1)}$ , and as  $\mathcal{T}(\vec{x}) \stackrel{lex}{\geq} \mathcal{T}(\vec{z})$  we conclude that  $z_{(1)} = z_{\pi(1)} = x_{\pi(1)}$ . Next, assuming that for some  $i < l$  and for all  $j < i$  we have  $z_{(j)} = z_{\pi(j)} = x_{\pi(j)}$ , then again as for all  $j \geq i$ ,  $z_{\pi(j)} \geq x_{\pi(i)}$ , and  $\mathcal{T}(\vec{x}) \stackrel{lex}{\geq} \mathcal{T}(\vec{z})$  we conclude that  $z_{(i)} = z_{\pi(i)} = x_{\pi(i)}$ . Hence, by induction we have proved that for all  $i < l$  we have  $z_{(i)} = z_{\pi(i)} = x_{\pi(i)}$ . Finally, since for all  $i \geq l$  we have  $z_{\pi(i)} > x_{\pi(l)}$ , hence  $z_{(i)} > x_{\pi(l)}$  we necessarily have that  $\mathcal{T}(\vec{z}) \stackrel{lex}{>} \mathcal{T}(\vec{x})$ , which brings us to the contradiction.

Therefore, we conclude that a leximin maximal vector on a set  $\mathcal{X}$  is also a max-min fair vector, and set  $\mathcal{X}$  is max-min achievable. ■

## B. Proof of Correctness of MP

The idea of the proof is the following. We first want to show that in every step we decrease the size of  $S^n$ , that is  $S^n \subset S^{n-1}$ . From this we will conclude that the algorithm finishes in at most  $N$  steps. We then show that what remains in the set  $R^n$  once the algorithm stops (that is  $S^n = \emptyset$ ), is the max-min fair allocation.

We will introduce several lemmas before proving the main theorem. Recall that the definitions of  $\mathcal{X}^n$ ,  $\mathcal{R}^n$ ,  $S^n$ ,  $T^n$  and  $MP^n$  are given in Section III-A

We first prove a lemma that illustrates the main idea of the algorithm, that in each steps we fix one by one the smallest coordinates of vectors to corresponding  $T$  values.

*Lemma 1:* For all  $n$  where  $T^n$  exists, for all  $x \in \mathcal{X}^n$ , and for all  $i \in S^{n-1} \setminus S^n$ , we have  $x_i = T^n$ . Furthermore, if for all  $m < n$  and for all  $i \in S^{m-1} \setminus S^m$  we have  $x_i = T^m$ , for all  $i \in S^n$  we have  $x_i \geq T^n$ , and for some  $i \in S^m$  we have  $x_i > T^m$ , then  $\vec{x} \in \mathcal{X}^n$ .

*Proof:* For  $n = 0$  we have  $S^0 = \{1, \dots, N\}$  and the result is trivial. Let us select arbitrary  $\vec{x} \in \mathcal{X}^n$ ,  $n > 0$ , and  $i \in S^n \setminus S^{n+1}$ . From the definition of  $\mathcal{X}^n$  we have for all  $i \in S^{n-1}$ ,  $x_i \geq T^n$ , and from the definition of  $S^n$  we have for all  $i \notin S^n$ ,  $x_i \leq T^n$ . Hence we have  $x_i = T^n$ .

For the second part, we also proceed by induction. Obviously  $\vec{x} \in \mathcal{X}^0$ . Suppose, for some  $m < n$ ,  $\vec{x} \in \mathcal{X}^{m-1}$ . Then it is easy to verify  $\vec{x}$  satisfies conditions from the definition of  $\mathcal{X}^m$ , hence  $\vec{x} \in \mathcal{X}^m$ . By induction, we verify that also  $\vec{x} \in \mathcal{X}^n$ . ■

Set  $\mathcal{X}^n$  is not compact by definition and we do not know if the maximum  $T^n$  of the problem  $MP^n$  exists. The following lemma is rather technical, and it proves the maximum always exists.

**Lemma 2:** If set  $\mathcal{X}$  is compact, then the maximum  $T^n$  of the problem  $MP^n$  exists for all  $n$ .

*Proof:* We start by induction. Since  $\mathcal{X}^0 = \mathcal{X}$  is compact, the maximum exists for  $n = 0$ . Suppose  $n > 0$ , and the claim holds for all  $m < n$ . Let us denote with  $T' = \sup_{\vec{x} \in \mathcal{X}^{n-1}} \min_{i \in S^{n-1}} x_i$ .  $T'$  always exists and  $T' > T^{n-1}$ . We proceed by contradiction. Suppose that the maximum does not exist hence  $T' \notin \mathcal{X}^n$ . By definition of  $T'$ , for every integer  $k > 0$  there exists  $\vec{x}^k \in \mathcal{X}^{n-1}$  such that  $T' - \min_{i \in S^{n-1}} x_i^k < 1/k$ .

We next want to select a subsequence of sequence  $\{\vec{x}^k\}$  such that for each member of the subsequence, the minimal component always has the same index, denoted by  $l$ . More formally, since  $S^{n-1}$  is a finite set, we can select  $l \in S^{n-1}$  such that there is an infinite subsequence  $\{\vec{x}^{k(l)}\} \in \mathcal{X}^{n-1}$  of sequence  $\{\vec{x}^k\}$  where for all  $k(l)$  we have  $\arg \min_{i \in S^{n-1}} x_i^{k(l)} = l$ .

This subsequence converges to  $\vec{x}' = \lim_{k(l) \rightarrow \infty} \vec{x}^{k(l)}$ . We have that  $\vec{x}' \in \mathcal{X}$  due to compactness of  $\mathcal{X}$ . By construction, we also have for all  $i \in S^{n-1}$ ,  $x'_i \geq x_l' = T' > T^{n-1}$ . By lemma 1 we have that for all  $i \notin S^{n-1}$ ,  $k_1(l), k_2(l)$ ,  $\vec{x}_i^{k_1(l)} = \vec{x}_i^{k_2(l)} = \vec{x}'_i$ , hence  $\vec{x}' \in \mathcal{X}^{n-1}$ , again by lemma 1. We see that vector  $\vec{x}'$  satisfies all the conditions of the definition of  $\mathcal{X}^n$ , hence it belongs to  $\mathcal{X}^n$  which leads to a contradiction. ■

We next show another property of the coordinates of vectors in  $\mathcal{X}^n$

**Lemma 3:** For all  $n$ ,  $\vec{x}, \vec{y} \in \mathcal{X}^n$  and  $t \in \{1, \dots, N\}$  such that  $x_t \leq T^n$ , we have  $y_t \geq x_t$ .

*Proof:* We prove lemma by induction over  $n$ . If  $n = 1$ , we have for all  $t$ ,  $x_t \geq T^1$  and  $y_t \geq T^1$ , hence for  $x_t = T^1$ , we have  $y_t \geq x_t$ . Next assume the above is true for  $n - 1$ . Suppose  $x_t <$

$T^n$ . We then also have  $x_t \leq T^{n-1}$ , hence by the induction assumption we have  $y_t \geq x_t$ . Finally, if for some  $t$ ,  $x_t = T^n$  then  $y_t \geq T^n$  or else we have a contradiction with the definition of  $T^n$ . ■

Finally, we show that in each step we keep the max-min fair vector in  $\mathcal{X}^n$  in order to show that in the last step, when we have a single point remaining, this point will indeed be the max-min fair one.

**Lemma 4:** If  $\vec{x}$  is max-min fair vector on  $\mathcal{X}$  then for all  $n$  such that  $\mathcal{X}^n \neq \emptyset$ ,  $\vec{x} \in \mathcal{X}^n$ . The same holds for  $\mathcal{R}^n$ .

*Proof:* We prove lemma by induction. If  $\vec{x} \notin \mathcal{X}^1$  then  $\vec{x}$  is not leximin maximal, hence the contradiction. Let us next assume  $\vec{x} \in \mathcal{X}^{n-1}$  and  $\vec{x} \notin \mathcal{X}^n$ , where  $\mathcal{X}^n \neq \emptyset$ . Then there exists  $\vec{y} \in \mathcal{X}^n$  and  $s \in S^n$  such that  $y_s > x_s$ . Also, by lemma 3, for all  $t \in \{1, \dots, N\}$  such that  $x_t \leq T^n$ , we have  $y_t \geq x_t$ . This contradicts the assumption that  $\vec{x}$  is max-min fair which proves the lemma. Since  $\mathcal{X}^n \subseteq \mathcal{R}^n$ , we have the second claim. ■

Now we are ready to prove the main theorem.

**Proof of theorem 2:** Let us call  $\vec{x}$  max-min fair vector on  $\mathcal{X}$ . From lemma 2 we know that the minimum  $T^n$  in  $MP^n$  is achieved. Therefore, there exist  $i^* \in S^{n-1}$ ,  $\vec{x}^* \in \mathcal{X}^{n-1}$  such that  $x_{i^*}^* = T^n$ , and we have  $i^* \notin S^n$ , thus we proved  $S^n \subset S^{n-1}$ . We conclude that sequence  $|S^n|$  decreases and we will have  $S^n = \emptyset$  in at most  $N$  steps.

We also notice that for every  $i \in \{1, \dots, N\}$  there exists  $m$  such that  $i \in S^{m-1}$  and  $i \notin S^m$ . From  $i \in S^{m-1}$  we have that for all  $\vec{x} \in \mathcal{X}^m$ ,  $x_i \leq T^m$ . From  $i \in S^m$  we have that for all  $x \in \mathcal{X}^{m-1}$  we have  $x_i \geq T^m$  in the constraints for  $MP^m$ . Now as for all  $n$ ,  $\mathcal{X}^n \subseteq \mathcal{X}^{n-1}$  we have that for all  $n \geq m$  and  $\vec{x} \in \mathcal{X}^n$  we have  $x_i = T^m$ . Once we have  $S^n = \emptyset$  it means that all components of vectors in  $\mathcal{R}^n$  are fixed hence  $|\mathcal{R}^n| = 1$ . According to lemma 4, this single vector in  $\mathcal{R}^n$  is also max-min fair on  $\mathcal{X}$ . ■

### C. Proof of Equality of MP and WF

**Proof of theorem 3:** Let us call  $T_{MP}^1$  the solution to the  $MP^1$  and  $T_{WF}^1$  the solution to the  $WF^1$ .  $T_{WF}^1$  is obviously achievable in  $MP^1$  so we have  $T_{MP}^1 \geq T_{WF}^1$ . Suppose that  $T_{MP}^1 > T_{WF}^1$ . This implies that for all  $s \in \{1, \dots, N\}$  we have  $(\vec{x}_{MP}^1)_s \geq T_{MP}^1$ . Due to the free-disposal property, we can successively decrease each of the components of  $\vec{x}$  larger than corresponding lower bound in  $\vec{m}$ , until arriving to a vector  $\vec{y}$ ,  $y_i = \max(T_{MP}^1, m_i)$ . This vector is

feasible, which contradicts the optimality of  $T_{WF}^1$ . The same reasoning can be applied to the successive algorithm steps, by decreasing the dimension of the feasible set. ■

## REFERENCES

- [1] A. Charny. An algorithm for rate allocation in a packet-switched network with feedback. *M.S. thesis*, MIT, May 1994.
- [2] A. Mas-Colell, M. Whinston, J. Green. *Microeconomic Theory*. Oxford University Press, 1995.
- [3] ATM Forum Technical Committee. "Traffic Management Specification - Version 4.0". *ATM Forum/95-0013R13*, February 1996.
- [4] W. Bossert and J.A. Weymark. Utility in social choice. In S. Barbera, P.J. Hammond, and C. Seidl, editors, *Handbook of Utility Theory*. Kluwer Academic Publishers, 2004.
- [5] M.A. Chen. Individual monotonicity and the leximin solution. *Economic Theory*, 15:353–365, 2000.
- [6] R. Cruz and A.V. Santhanam. Optimal routing, link scheduling and power control in multi-hop wireless networks. In *Proceedings INFOCOM'03*, 2003.
- [7] D. Bertsekas and R. Gallager. *Data Networks*. Prentice-Hall, 1987.
- [8] D. Rubenstein, J. Kurose, D. Towsley. "The Impact of Multicast Layering on Network Fairness". *IEEE/ACM Transactions on Networking*, 10(2):169–182, Apr. 2002.
- [9] E. Hahne. "Round-Robin Scheduling for Max-Min Fairness in Data Networks". *IEEE Journal on Selected Areas in Communications*, 9(7):1024–1039, Sept. 1991.
- [10] H. Tzeng and K. Siu. "On Max-Min Fair Congestion Control for Multicast ABR Service in ATM". *IEEE Journal on Selected Areas in Communications*, 15(3):545–556, April 1997.
- [11] J. Byers, et al. "A Digital Fountain Approach to Reliable Distribution of Bulk Data". In *ACM SIGCOMM '98*, September 2-4 1998.
- [12] J. Ros and W. Tsai. "A Theory of Convergence Order of Maxmin Rate Allocation and an Optimal Protocol". In *INFOCOM'01*, pages 717–726, 2001.
- [13] J.H. Chang and L. Tassiulas. "Energy Conserving Routing in Wireless Ad-hoc Networks". In *INFOCOM'00*, pages 22–31, 2000.
- [14] L. Georgiadis, et al. "Lexicographically Optimal Balanced Networks". In *INFOCOM'01*, pages 689–698, 2001.
- [15] L. Tassiulas and S. Sarkar. "Maxmin Fair Scheduling in Wireless Networks". In *INFOCOM'02*, 2002.
- [16] A.L. McKellips and S. Verdu. Maximin performance of binary-input channels with uncertain noise distributions. *IEEE Transactions on Information Theory*, 44(3):947–972, May 1998.
- [17] P. Marbach. "Priority Service and Max-Min Fairness". In *INFOCOM'02*, 2002.
- [18] B. Radunović and J. Y. Le Boudec. Optimal power control, scheduling and routing in UWB networks. *IEEE Journal on Selected Areas in Communications*, September 2004.
- [19] B. Radunovic and J.-Y. Le Boudec. Power control is not required for wireless networks in the linear regime. In *WoWMoM*, June 2005.
- [20] B. Radunović and J.-Y. Le Boudec. A unified framework for max-min and min-max fairness with applications. *Technical report LCA-REPORT-2006-001*, EPFL, January 2006.
- [21] J. Rawls. *A Theory of Justice*. Harvard University Press, 1971.
- [22] V. Rodoplu and T.H. Meng. Minimum energy mobile wireless networks. *IEEE J. Select. Areas Commun.*, 17(8):1333 – 1344, August 1999.
- [23] S. Sarkar and L. Tassiulas. "Fair Allocation of Discrete Bandwidth Layers in Multicast Networks". In *INFOCOM'00*, pages 1491–1500, 2000.
- [24] J. Van Leeuwen. Graph algorithms. In J. Van Leeuwen, editor, *Algorithms and Complexity*. Elsevier, 1992.
- [25] M. Win and R. Scholtz. Ultra-wide bandwidth time-hopping spread-spectrum impulse radio for wireless multiple-access communications. *IEEE Transactions on Communications*, 48(4):679–691, April 2000.
- [26] Xiao Long Huang, Brahim Bensaou. "On Max-min Fairness and Scheduling in Wireless Ad-Hoc Networks: Analytical Framework and Implementation". In *Proceedings MobiHoc'01*, Long Beach, California, October 2001.
- [27] Y. Hou, H. Tzeng, S. Panwar. "A Generalized Max-Min Rate Allocation Policy and Its Distributed Implementation Using the ABR Flow Control Mechanism". In *INFOCOM'98*, pages 1366–1375, 1998.
- [28] Z. Cao and E. Zegura. "Utility Max-Min: An Application-Oriented Bandwidth Allocation Scheme". In *INFOCOM'99*, pages 793–801, 1999.



**Božidar Radunović** received B.S. degree in electrical engineering from the University of Belgrade, School of Electrical Engineering, Serbia, in 1999, and he received his doctorate in 2005 at EPFL, Switzerland. He participated in the Swiss NCCR project terminodes.org. His interests are in the architecture and performance of wireless ad-hoc networks.



**Jean-Yves Le Boudec** (Fellow, 2004) graduated from Ecole Normale Supérieure de Saint-Cloud, Paris, received his doctorate in 1984 from the University of Rennes, France. In 1987 he joined Bell Northern Research, Ottawa, Canada, as a member of scientific staff in the Network and Product Traffic Design Department. In 1988, he joined the IBM Zurich Research Laboratory where he was manager of the Customer Premises Network group. In 1994 he became professor at EPFL, where he is now full professor. He is co-author of the book "Network Calculus". His interests are in the architecture and performance of communication systems.